

Rewind® Dilour

Latex-free event carpet, 100% recyclable
into a pure high-grade recycle



REWIND®



TECHNICAL DATA	TECHNISCHE DATEN	FICHE TECHNIQUE		
Manufacturing process	Herstellungsart	Méthode de fabrication	DIN 61151	Needle felt
Surface structure	Oberflächenstruktur	Aspect de surface	-	Dilour
Pile material	Polmaterial	Composition des fibres	-	100% polypropylene
Pile weight Total weight	Polgewicht Gesamtgewicht	Poids des fibres Poids total	ISO 8453	460 g/m ²
Roll length	Rollenlänge	Longueur rouleau	-	40 m
Backing	Rückenbeschichtung	Dossier	ISO 2424	None - latex free
Pile height	Polhöhe	Hauteur du velours	-	2,5 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	4,2 mm
Permanent anti-static	Permanent antistatisch	Antistatique permanent	ISO 6356	≤ 2kV
Fire Classification	Brennklasse	Comportement au feu	EN 13501-1	Bfl-s1
Prodis GUT Certificate	Prodis GUT Zertifikat	Certificat Prodis GUT	-	943358A6



CONTACT

rewind@bintg.com
www.rewindcarpet.com

A BRAND OF
**Beaulieu
International
Group**

